

Construction Products Regulation 305/2011

Declaration of Performance

No. WTK/SFT/KBWTP

WT Knowles & Sons Limited

Manufacturer

W T Knowles & Sons Limited

Ash Grove Pipe Works
Elland
West Yorkshire
HX5 9|A

www.wtknowles.co.uk

Open-Topped Flue Terminal

Bradford Windguard Push On Top KBWTP

Dimensions

Base:	Outside diameter	310mm
	Inside diameter	280mm
Тор:	Outside diameter	275mm
	Inside diameter	230mm

Height:	KBWTP
mm	550



Intended Use

To be fixed onto an existing chimney pot or flue liner to convey combustion gases from a solid fuel fire safely into the atmosphere

Compliance

Conforms to harmonised standard: BS EN 13502:2002 Type 0 - open-topped flue terminal

Annex ZA.I Attestation of conformity system - 4

Performance Characteristic

Flow Resistance (K): NPD

Durability: Freeze/Thaw Pass - BSI Test Report 8422446

Dangerous Substances: Not applicable

OD / ID / HT WTK DATE (DDMMYY)

The performance of the products described above is in conformity with the declared Performance Characteristic when installed and used in accordance with the manufacture's instructions.

This declaration is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by: Martin Knowles Managing Director

Elland 4th June 2018
Place and Date of Issue

