

Construction Products Regulation 305/2011

Declaration of Performance

WT Knowles & Sons Limited

No. WTK/SFT/KRPI

Manufacturer

W T Knowles & Sons Limited

Ash Grove Pipe Works
Elland
West Yorkshire
HX5 9|A

www.wtknowles.co.uk

Open-Topped Flue Terminal

Ryburn Pot KRPI



Base:	Outside diameter	330mm
	Inside diameter	295mm
Тор:	Outside diameter	280mm
	Inside diameter	240mm

Height:	KRPI
mm	1090



Intended Use

To be fixed on a masonry chimney stack, over the flue liner, to convey combustion gases from a solid fuel fire safely into the atmosphere

Compliance

Conforms to harmonised standard: BS EN 13502:2002 Type 0 - open-topped flue terminal

Annex ZA.I Attestation of conformity system - 4

Performance Characteristic

Flow Resistance (K): NPD

Durability: Freeze/Thaw Pass - BSI Test Report 8422446

Dangerous Substances: Not applicable

Markings WTK EN 13502 Type 0 €

OD / ID / HT WTK DATE (DDMMYY)

The performance of the products described above is in conformity with the declared Performance Characteristic when installed and used in accordance with the manufacture's instructions.

This declaration is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by: Martin Knowles Managing Director

Elland 4th June 2018
Place and Date of Issue

