

Construction Products Regulation 305/2011

Declaration of Performance

WT Knowles & Sons Limited

No. WTK/SFT/KYMII - KYMI70

Manufacturer

W T Knowles & Sons Limited

Ash Grove Pipe Works
Elland
West Yorkshire
HX5 9|A

www.wtknowles.co.uk

Open-Topped Flue Terminal

Cannon Head Pot KYMII - KYMI70



Dimensions

Base:	Outside diameter	300mm		
	Inside diameter	260mm		
Тор:	Outside diameter	275mm		
	Inside diameter	210mm		

Height:	KYMII	KYM12	KYM13	KYM14	KYMI50	KYMI60	KYMI70
mm	300	375	450	600	750	900	1,200

Intended Use

To be fixed onto a masonry chimney stack, over the flue liner, to convey combustion gases from a solid fuel fire safely into the atmosphere

Compliance

Conforms to harmonised standard: BS EN 13502:2002 Type 0 - open-topped flue terminal

Annex ZA.I Attestation of conformity system - 4

Performance Characteristic

Flow Resistance (K): NPD

Durability: Freeze/Thaw Pass - BSI Test Report 8422446

Dangerous Substances: Not applicable

OD / ID / HT WTK DATE (DDMMYY)

The performance of the products described above is in conformity with the declared Performance Characteristic when installed and used in accordance with the manufacture's instructions.

This declaration is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by: Martin Knowles Managing Director

Elland 4th June 2018 Place and Date of Issue

